

DEHUMIDIFIERS

AQUARIA SLIM 10 P

AQUARIA SLIM 10 P Cod. 01939



FEATURES

Dehumidification capacity: 10 l/24h⁽¹⁾
Tank capacity: 2 l
Constant condensation disposal
Defrosting device
Ambient humidity display
Air filter
Full tank alarm
Ergonomic handle
Wheels
Maximum volume of dehumidification: 100 m³



SLIM DESIGN

Only 185 mm thickness.



DIGITAL TOUCH DISPLAY

For precision commands.



SEMI-TRANSPARENT TANK

To view the water level.



PRACTICAL

Thanks to the handle and the transportable wheels.



AQUARIA SLIM 10 P		
	Code	01939
	EAN	8021183019391
Dehumidification capacity (1)	l/24h	5.4
Dehumidification capacity (2)	l/24h	10
Dehumidifiable volume	m ³	100
Power absorption in dehumidification mode (1)	W	280
Max. power absorption in dehumidification mode (2)	W	262
Max. absorption in dehumidification mode (2)	A	1,39
Protection level		IP 20
Fan speeds		1
Tank capacity	l	2,0
Air volume (max)	m ³ /h	120
Dimensions (W x H x D with wheels)	mm	276X500X185
Packing dimensions (W x H x D)	mm	315X555X215
Noise level	dB(A)	42
Weight (without packing)	kg	9,5
Weight (with packing)	kg	10,4
Refrigerant gas	Tipo-Type	R290
Global warming potential of refrigerant GWP	kgCO2 eq.	3
Refrigerant gas charge	kg	0,045
Plug		SCHUKO
Power supply	V-F-Hz	220-240 - 1 - 50
Power supply min - max	V	207- 254
Fuse		2 AT
Conformity Mark		CE
Air filter		✓
Carbon filter		
Continuous operation with hose		✓
Dehumidistat		✓
Humidity level power settings		✓
Indoor humidity visualizer		✓
Indoor temperature visualizer		
Tank full light		✓
Defrosting device		✓
Heating function with adjustable temperature		
Dehumidifying + heating function		

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)

*hermetically sealed equipment containing fluorinated gas GWP 1430

AQUARIA SILENT 14

AQUARIA SILENT 14 Cod. 01667



FEATURES

Dehumidification capacity: 14l*/24h
Tank capacity: 2 l
Sound level: only 36 dB (A)
Full tank alarm
Continuous operation with hose
Electronic defrosting device
Visible water level - transparent tank
Handle
Dehumidifiable volume: 120-140 m³



SILENT SYSTEM

Aquaria Silent 14 is among the quietest dehumidifiers in its category, more than 10% quieter with a sound level of only

36 dB (A)



QUICK CONTROL

Extremely easy to use mechanical control to adjust room humidity.



(1) 32° C – 80 %RH

(2) Internal tests on the range Olimpia Splendid

		AQUARIA SILENT 14
	Code	01667
	EAN	8021183016673
Dehumidification capacity (1)	l/24h	6,2
Dehumidification capacity (2)	l/24h	14
Dehumidifiable volume	m³	120
Heating capacity	W	-
Power absorption in dehumidification mode (1)	W	172
Max. power absorption in dehumidification mode (2)	W	214
Max. power absorption in dehumidification+heating mode (2)	W	-
Fan speeds		1
Tank capacity	l	2
Air volume (max)	m³/h	80
Dimensions (W x H x D)	mm	307 x 427 x 258
Noise level	db(A)	36
Weight	Kg	12,8
Refrigerant gas / charge	Type / kg	R134A / 0,110 / 1430
Power supply	V-F-Hz	230 - 1 - 50
Power supply min - max	V	216/244
Air filter		✓
Carbon filter		
Photocatalytic filter		
HEPA filter		
Continuous operation with hose		✓
Mechanical controls		✓
Digital control		
Mechanical humidistat		✓
Electronic humidistat		
LCD Display		
Backlit liquid crystal display		
Indoor humidity visualizer		
Indoor temperature visualizer		
Tank full light		✓
Defrosting device		✓
Hot gas defrosting system		
Dehumidifying + heating function		
Handle		✓
Wheels		✓
Concealed tank with push-pull panel		
Water tank with handle		
Visible water level		✓
Wall mounting kit		

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)


*hermetically sealed equipment containing fluorinated gas GWP 1430



Design by Ercoli & Garlandini

FEATURES

Dehumidification capacity: 16 l*/24h
 Tank capacity: 1,8 l
 Sound power: 40 dB (A)
 Digital control
 Drying mode: constant and fast dehumidification
 LCD Display
 Full tank alarm
 Constant condensation disposal
 Electronic defrosting device
 visible water level and transparent tank
 Handle
 Wheels
 Maximum volume of dehumidification: 120-140 m³



PURE SYSTEM

Mechanic air filtration system, for better air quality.



EASY TO USE

Equipped with barycentric and ergonomic handle, and wheels for easier transport.



DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode, Equipped with back-lit LCD display to view humidity level and ambient temperature.



COMPACT TECHNOLOGY

In just 25 cm of depth and a height of 45 cm, a dehumidification capacity of 16 l/24h.



TURBO/DRYING

This function optimizes the laundry's drying process by constantly operating the dehumidifier at full power.



(1) 32° C – 80 %RH

		AQUARIA 16
	Code	01440
	EAN	8021183014402
Dehumidification capacity (1)	l/24h	6,5
Dehumidification capacity (2)	l/24h	16
Humidifiable Area	m³	-
Heating power	W	-
Power consumption in dehumidification (1)	W	243
Max Power consumption in dehumidification (2)	W	312
Max Power consumption in dehumidification + heating (2)	W	-
Fan speed		1
Tank capacity	l	1,8
Air flow rate (max)	m³/h	170
Dimensions (Width x H x Depth)	mm	305X464X261
Sound level	db(A)	40
Weight	Kg	12
Refrigerant gas / Charge / GWP*	Type / kg	R410A / 0,130 / 1430
Power supply	V-F-Hz	230 - 1 - 50
Minimum/maximum power supply voltage	V	216/244
Air filter		✓
Active carbon filter		
Fotocatalytic filter		
HEPA filter		
Operation with continuous drain		✓
Mechanical controls		
Electronic controls		✓
Mechanical Humidostat		
Digital Humidostat		✓
LCD Display		✓
Backlight LED Display		
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Tank full light		✓
Defrosting device		✓
Mot gas defrosting system		✓
Dehumidifying + heating function (with electrical resistance)		
Handle		✓
Wheels		✓
Tank with push-pull locking		
Tank with handle		
Visible water level		✓
Wall mounting kit		

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)


*hermetically sealed equipment containing fluorinated gas GWP 1430



Design by Ercoli & Garlandini

FEATURES

Dehumidification capacity: 16 l/24h⁽¹⁾
 Tank capacity: 1,8 l
 Electrical Resistance 1000W
 Sound power: 40 dB (A)
 Digital control
 Drying mode: constant and fast dehumidification
 LCD Display
 Full tank alarm
 Constant condensation disposal
 Electronic defrosting device
 visible water level and transparent tank
 Handle
 Wheels
 Maximum volume of dehumidification: 120-140 m³



PURE SYSTEM

Mechanic air filtration system, for better air quality.



SUPER DEHUMIDIFICATION

Combines dehumidification with heating thanks to a 1000 W electrical element that significantly reduces dehumidification time.



DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode. Equipped with back-lit LCD display to view humidity level and ambient temperature.



COMPACT TECHNOLOGY

In just 25 cm of depth and a height of 45 cm, a dehumidification capacity of 16 l/24h.



EASY TO USE

Equipped with barycentric and ergonomic handle, and wheels for easier transport.



TURBO/DRYING

This function optimizes the laundry's drying process by constantly operating the dehumidifier at full power.



(1) 32° C – 80 %RH

		AQUARIA 16T
	Code	01446
	EAN	8021183014464
Dehumidification capacity (1)	l/24h	6,5
Dehumidification capacity (2)	l/24h	16
Humidifiable Area	m³	120-140
Heating power	W	1000
Power consumption in dehumidification (1)	W	243
Max Power consumption in dehumidification (2)	W	312
Max Power consumption in dehumidification + heating (2)	W	-
Fan speed		1
Tank capacity	l	1,8
Air flow rate (max)	m³/h	170
Dimensions (Width x H x Depth)	mm	305X464X261
Sound level	db(A)	40
Weight	Kg	12
Refrigerant gas / Charge / GWP*	Type / kg	R410A / 0,130 / 1430
Power supply	V-F-Hz	230 - 1 - 50
Minimum/maximum power supply voltage	V	216/244
Air filter		√
Active carbon filter		
Fotocatalytic filter		
HEPA filter		
Operation with continuous drain		√
Mechanical controls		
Electronic controls		√
Mechanical Humidostat		
Digital Humidostat		√
LCD Display		√
Backlight LED Display		
Indoor humidity visualizer		√
Indoor temperature visualizer		√
Tank full light		√
Defrosting device		√
Mot gas defrosting system		√
Dehumidifying + heating function (with electrical resistance)		√
Handle		√
Wheels		√
Tank with push-pull locking		
Tank with handle		
Visible water level		√
Wall mounting kit		

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)


*hermetically sealed equipment containing fluorinated gas GWP 1430



Design by King & Miranda

FEATURES

Dehumidification capacity: 22 l/24h⁽¹⁾
 Tank capacity: 3.5 l
 Digital control
 LCD Display
 Full tank alarm
 Constant condensation disposal
 Electronic defrosting device
 Hidden tank with push-pull closing panel
 Water tank with handle, for easier transport and emptying
 Visible water level
 Hidden handle
 Wheels
 Cable winder
 Maximum volume of dehumidification: 120-140 m³



PURE SYSTEM 3

Triple filtration system which combines the filter with activated carbons (eliminates odors and deactivates any potentially harmful gases) HEPA filter (retains fine dust with a few microns diameter) Photo catalytic filter (sterilizes air by eliminating a high percentage of viruses and bacteria).



NON-STOP OPERATING

The constant condensation disposal, which can be selected on the control panel, allows uninterrupted dehumidification.



DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode; moreover, Aquaria is equipped with back-lit LCD display to view humidity level and ambient temperature.



BACK CABLE WINDER

Cable winder to tidily put the product away.



LARGE TANK

The tank contains 3.5 l and it can be easily extracted.

(1) 32° C – 80 %RH

		AQUARIA 22
	Code	01644
	EAN	8021183016444
Dehumidification capacity (1)	l/24h	13, 5
Dehumidification capacity (2)	l/24h	22
Dehumidifiable Area	m²	120/140
Heating power	W	-
Power consumption in dehumidification (1)	W	250
Max Power consumption in dehumidification (2)	W	295
Max Power consumption in dehumidification + heating (2)	W	-
Fan speed		1
Tank capacity	l	3,5
Air flow rate (max)	m³/h	230
Dimensions (Width x H x Depth)	mm	280 x 545 x 385
Sound level	db(A)	40
Weight	Kg	17
Refrigerant gas / Charge / GWP*	Type / kg	R134A / 0,175 / 1430
Power supply	V-F-Hz	230 - 1 - 50
Minimum/maximum power supply voltage	V	198 / 264
Air filter		✓
Active carbon filter		✓
Fotocatalytic filter		✓
HEPA filter		✓
Operation with continuous drain		✓
Mechanical controls		
Electronic controls		✓
Mechanical Humidostat		
Digital Humidostat		✓
LCD Display		✓
Backlight LED Display		
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Tank full light		✓
Defrosting device		✓
Mot gas defrosting system		
Dehumidifying + heating function (with electrical resistance)		
Handle		✓
Wheels		✓
Tank with push-pull locking		✓
Tank with handle		✓
Visible water level		✓
Wall mounting kit		

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)

*hermetically sealed equipment containing fluorinated gas GWP 1430

AQUARIA THERMO 22


AQUARIA THERMO 22 Cod. 01645



Design by King & Miranda

FEATURES

Dehumidification capacity: 22l/24h⁽¹⁾
Tank capacity: 3,5 l
Electrical Resistance 1000W
Digital control
LCD Display
Full tank alarm
Constant condensation disposal
Electronic defrosting device
Hidden tank with push-pull closing panel
Water tank with handle, for easier transport and emptying
Visible water level
Handle
Wheels
Maximum volume of dehumidification: 120-140 m³



PURE SYSTEM 3

Triple filtration system which combines the filter with activated carbons (eliminates odors and deactivates any potentially harmful gases) HEPA filter (retains fine dust with a few microns diameter)

Photo catalytic filter (sterilizes air by eliminating a high percentage of viruses and bacteria).



SUPER DEHUMIDIFICATION

Combines dehumidification with heating thanks to a 1000 W electrical element that significantly reduces dehumidification time.



BACK CABLE WINDER

Cable winder to tidily put the product away.



DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode; moreover, AquaThermo is equipped with back-lit LCD display to view humidity level and ambient temperature.



(1) 32° C – 80 %RH

AQUARIA THERMO 22		
	Code	01645
	EAN	8021183016451
Dehumidification capacity (1)	l/24h	13,5
Dehumidification capacity (2)	l/24h	22
Dehumidifiable Area	m³	200
Heating power	W	1000
Power consumption in dehumidification (1)	W	250
Max Power consumption in dehumidification (2)	W	295
Max Power consumption in dehumidification + heating (2)	W	1315
Fan speed		1
Tank capacity	l	3,5
Air flow rate (max)	m³/h	250
Dimensions (Width x H x Depth)	mm	280 x 545 x 385
Sound level	db(A)	40
Weight	Kg	17
Refrigerant gas / Charge / GWP*	Type / kg	R134A / 0,175 / 1430
Power supply	V-F-Hz	230 - 1 - 50
Minimum/maximum power supply voltage	V	198 / 264
Air filter		✓
Active carbon filter		✓
Fotocatalytic filter		✓
HEPA filter		✓
Operation with continuous drain		✓
Mechanical controls		
Electronic controls		✓
Mechanical Humidostat		
Digital Humidostat		✓
LCD Display		✓
Backlight LED Display		✓
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Tank full light		✓
Defrosting device		✓
Mot gas defrosting system		
Dehumidifying + heating function (with electrical resistance)		✓
Handle		✓
Wheels		✓
Tank with push-pull locking		✓
Tank with handle		✓
Visible water level		✓
Wall mounting kit		

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)


*hermetically sealed equipment containing fluorinated gas GWP 1430



Design by King & Miranda

FEATURES

- Dehumidification capacity: 28l/24h⁽¹⁾
- Tank capacity: 3.5 l
- Digital control
- LCD Display
- Full tank alarm
- Constant condensation disposal
- Electronic defrosting device
- Hidden tank with push-pull closing panel
- Water tank with handle, for easier transport and emptying
- Visible water level
- Hidden handle
- Wheels
- Cable winder
- Maximum volume of dehumidification: 240 m³



PURE SYSTEM 3


Triple filtration system which combines the filter with activated carbons (eliminates odors and deactivates any potentially harmful gases) HEPA filter (retains fine dust with a few microns diameter)

Photo catalytic filter (sterilizes air by eliminating a high percentage of viruses and bacteria).



DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode; moreover, AquaRIA is equipped with back-lit LCD display to view humidity level and ambient temperature.



(1) 32° C – 80 %RH

		AQUARIA 28
	Code	01646
	EAN	8021183016468
Dehumidification capacity (1)	l/24h	15
Dehumidification capacity (2)	l/24h	28
Dehumidifiable Area	m³	240
Heating power	W	-
Power consumption in dehumidification (1)	W	425
Max Power consumption in dehumidification (2)	W	510
Max Power consumption in dehumidification + heating (2)	W	-
Fan speed		1
Tank capacity	l	3,5
Air flow rate (max)	m³/h	285
Dimensions (Width x H x Depth)	mm	280 x 545 x 385
Sound level	db(A)	42
Weight	Kg	18
Refrigerant gas / Charge / GWP*	Type / kg	R134A / 0,160 / 1430
Power supply	V-F-Hz	230 - 1 - 50
Minimum/maximum power supply voltage	V	207 / 264
Air filter		✓
Active carbon filter		✓
Fotocatalytic filter		✓
HEPA filter		✓
Operation with continuous drain		✓
Mechanical controls		
Electronic controls		✓
Mechanical Humidostat		
Digital Humidostat		✓
LCD Display		✓
Backlight LED Display		✓
Indoor humidity visualizer		✓
Indoor temperature visualizer		✓
Tank full light		✓
Defrosting device		✓
Mot gas defrosting system		
Dehumidifying + heating function (with electrical resistance)		
Handle		✓
Wheels		✓
Tank with push-pull locking		✓
Tank with handle		✓
Visible water level		✓
Wall mounting kit		

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)

*hermetically sealed equipment containing fluorinated gas GWP 1430



Design by King & Miranda

FEATURES OF SECCOPROF 28

Dehumidification capacity: 22 l/24h⁽¹⁾
 Tank capacity: 3.5 l
 Digital control
 LCD Display
 Visible water level
 Full tank alarm
 Double handle
 Wheels
 Maximum volume of dehumidification: 250 m³

FEATURES OF SECCOPROF 38

Dehumidification capacity: 38 l/24h⁽¹⁾
 Tank capacity: 10 l
 Warm gas defrosting
 Digital control
 LCD Display
 Visible water level
 Full tank alarm
 Double handle
 Wheels
 Maximum volume of dehumidification: 330 m³



SUPER POWER

The products in the SeccoProf range are extremely powerful, and they can absorb up to 38 l of excess humidity per day, thus allowing to dehumidify large spaces.



NON-STOP OPERATING

The constant condensation disposal, which can be selected on the control panel, allows uninterrupted dehumidification.



DIGITAL CONTROL

Multifunction electronic panel, to set the desired humidity level and activate the Drying mode; moreover, Aquaria is equipped with back-lit LCD display to view humidity level and ambient temperature.



WARM GAS DEFROSTING

Guarantees a constant operation of the compressor, avoiding frequent activation and deactivation periods. It also allows the product to work even near 0°C⁽²⁾.



IRON SHAPE

Its metal frame makes the Seccoprof range solid and corrosion- and impact-resistant.

(1) 32° C – 80 %RH

(2) Only model SeccoProf 38

		SECCOPROF 28	SECCOPROF 38
	Code	01208	01209
	EAN	8021183012088	8021183012095
Dehumidification capacity (1)	l/24h	15	20
Dehumidification capacity (2)	l/24h	28	38
Humidifiable Area	m³	250	330
Heating power	W		
Power consumption in dehumidification (1)	W	450	500
Max Power consumption in dehumidification (2)	W	550	585
Max Power consumption in dehumidification + heating (2)	W		
Fan speed		1	1
Tank capacity	l	10	10
Air flow rate (max)	m³/h	340	350
Dimensions (Width x H x Depth)	mm	310 x 650 x 435	310 x 650 x 435
Sound level	db(A)	47	49
Weight	Kg	23	25
Refrigerant gas / Charge / GWP*	Type / kg	R410A / 0,260 / 1430	R410A / 0,330 / 1430
Power supply	V-F-Hz	230 - 1 - 50	230 - 1 - 50
Minimum/maximum power supply voltage	V	198 / 264	198 / 244
Air filter		✓	✓
Active carbon filter			
Fotocatalytic filter			
HEPA filter			
Operation with continuous drain		✓	✓
Mechanical controls			
Electronic controls		✓	✓
Mechanical Humidostat			
Digital Humidostat		✓	✓
LCD Display		✓	✓
Backlight LED Display			
Indoor humidity visualizer		✓	✓
Indoor temperature visualizer		✓	✓
Tank full light		✓	✓
Defrosting device		✓	
Mot gas defrosting system			✓
Dehumidifying + heating function (with electrical resistance)			
Handle		✓	✓
Wheels		✓	✓
Tank with push-pull locking			
Tank with handle			
Visible water level		✓	✓
Wall mounting kit			

(1) DB 27°C - WB 21°C (27°C - 60% RH)

(2) DB 32°C - WB 29°C (32°C - 80% RH)

*hermetically sealed equipment containing fluorinated gas GWP 1430