



**TRANE**



## Conquest CXAX Air-to-Water Heat Pump



**TRANE**  
TECHNOLOGIES

**E CELLENT**  
Trane heating.  
Naturally.



## Conquest CXAX Air-to-Water Heat Pump



**Cooling capacity: 40-155 kW**

**Heating capacity: 40-155 kW**

- Compact design: reduced footprint and low-profile design
- Reversible operation: cooling or heating
- Optimized for R454B low GWP refrigerant and high seasonal efficiency
- Low sound levels with no compromise on efficiency
- Wide operating map: down to -15°C ambient air and up to +60°C leaving hot water temperature
- Single and/or dual circuit

# CONQUEST


## The most sustainable and best value R454B heat pump

Comfort, sustainability and economy are primary concerns when selecting HVAC equipment for your building. Trane Conquest heat pumps combine high performance and proven reliability in a compact and affordable design, delivering maximum value.

CXAX can heat or cool down your building all year round, whether the outdoor air temperature is -15°C or +46°C. Units can deliver up to 60°C hot water temperature.

## Low noise - with no compromise on efficiency

Operating noise can be a significant disturbance in sensitive building environments. Most manufacturers oversize their units in order to reduce sound power levels. Trane's Conquest range has been designed to deliver lower noise, without reducing efficiency or affecting the footprint. Low Noise (LN) models achieve an impressive 47 dB(A) sound pressure level at 10m in free field.



### Smart and simple

Operation is easy thanks to the integrated Trane Symbio™ 800 controller with optional LCD interface.

Communication interfaces are available to provide connectivity with Modbus, BACnet® and Trane BMS.



### Range description

- Trane Conquest heat pumps are available in 14 sizes. Units are available with single and/or dual circuit (on 90-155 kW range), as well two acoustic packages: Standard Noise, Low Noise (with no loss of efficiency).

### Technical specifications

<b>Cooling capacity</b>	40-155 kW
<b>Heating capacity</b>	40-155 kW
<b>Eurovent certification</b>	●
<b>ErP Certification</b>	●
<b>Refrigerants</b>	R454B   R410A
<b>Operating mode</b>	Cooling only   Heat pump
<b>Energy saving</b>	Heat recovery
<b>Compressor</b>	Scroll

## Product data

### CXAX

	Pc (1) kW	Pec (1) kW	EER (1)	SEER (2)	$\eta_{sc}$ (2) %	Ph (3) kW	Peh (3) kW	COP (3)	Ph (4)	Peh (4) kW	COP (4)	SCOP (5)	$\eta_{sh}$ (5) %	LwO (6) dB(A)	Refrigerant (7) mm	W (7) mm	H (7) mm	OW (4) kg	
<b>CXAX 015 SE SN</b>	38,8	13,7	2,83	4,29	168,5	41,3	14,1	2,93	-	-	-	3,21	125,3	84	R454B	2346	1285	1747	558
<b>CXAX 017 SE SN</b>	44,0	16,1	2,74	4,34	170,5	47,5	16,0	2,97	-	-	-	3,28	128,2	84	R454B	2346	1285	1747	564
<b>CXAX 020 SE SN</b>	54,9	18,1	3,03	4,20	164,9	55,0	18,6	2,96	-	-	-	3,21	125,4	88	R454B	2346	1285	1747	616
<b>CXAX 023 SE SN</b>	61,5	20,8	2,95	4,31	169,6	61,9	20,2	3,07	-	-	-	3,22	125,8	88	R454B	2346	1285	1747	644
<b>CXAX 026 SE SN</b>	67,8	23,9	2,84	4,13	162,3	68,5	22,5	3,05	-	-	-	3,27	127,9	88	R454B	2346	1285	1747	649
<b>CXAX 030 SE SN</b>	74,7	26,5	2,82	4,09	160,7	77,3	25,0	3,09	-	-	-	3,36	131,5	88	R454B	2346	1285	1947	684
<b>CXAX 036 SE SN</b>	89,2	30,7	2,91	4,74	186,5	92,8	29,8	3,12	-	-	-	3,50	137,0	87	R454B	2326	2250	1747	911
<b>CXAX 039 SE SN</b>	102,3	34,3	2,98	4,54	178,4	105,2	34,1	3,09	-	-	-	3,36	131,5	87	R454B	2326	2250	1747	954
<b>CXAX 045 SE SN</b>	111,2	39,0	2,85	4,39	172,5	116,3	37,9	3,07	-	-	-	3,41	133,3	90	R454B	2326	2250	1747	972
<b>CXAX 035 SE SN</b>	92,2	32,1	2,87	4,47	175,7	95,1	31,6	3,01	-	-	-	3,38	132,2	87	R454B	2327	2250	1747	1000
<b>CXAX 040 SE SN</b>	108,4	35,8	3,03	4,32	169,8	110,0	37,3	2,95	-	-	-	3,20	125,2	91	R454B	2327	2250	1747	1098
<b>CXAX 046 SE SN</b>	121,2	41,5	2,92	4,28	168,3	124,0	42,2	2,94	-	-	-	3,24	126,6	91	R454B	2327	2250	1747	1098
<b>CXAX 052 SE SN</b>	136,7	47,3	2,89	4,31	169,4	137,1	45,7	3,00	-	-	-	3,35	130,9	91	R454B	2327	2250	1747	1120
<b>CXAX 060 SE SN</b>	150,4	52,6	2,86	4,28	168,1	155,5	51,8	3,00	-	-	-	3,41	133,4	91	R454B	2327	2250	1947	1190

Pc: Cooling capacity

SEER: Seasonal Energy Efficiency Ratio

Peh: Total power input in heating

$\eta_{sh}$ : Seasonal space heating energy efficiency

L: Length

OW : Operating Weight

Pec: Total power input in cooling

$\eta_{sc}$ : Seasonal space cooling energy efficiency

COP: Coefficient Of Performance (heating)

LwO: A-weighted sound power level outside

W: Width

EER: Energy Efficiency Ratio (cooling)

Ph: Heating capacity

SCOP: Seasonal Coefficient Of Performance

Refrigerant: Refrigerant type

H: Height

(1): Cooling: outdoor air temperature 35°C and chilled water temperature 12°C/7°C. (EN 14511:2022)

(2): Ecodesign rating for comfort chiller - Fan coil application. Outdoor air temperature 35°C and chilled water temperature in/ out: 12°C/7°C.  $\eta_{sc}$ ,c/SEER as defined in Ecodesign requirements for Comfort Chillers with 2000 kW maximum capacity - REGULATION (EU) N° 2016/2281 of 20 December 2016.

(3): Outdoor air temperature 7°C - hot water temperature in/out 40/45°C. (EN 14511:2022)

(4): Outdoor air temperature 7°C - hot water temperature in/out 30/35°C. (EN 14511:2022)

(5): Ecodesign rating at low temperature conditions. Outdoor temperature: 7°C dry bulb/6°C wet bulb and hot water temperature in/out: 30°C/35°C.  $\eta_{s,h}$  / SCOP as defined in Directive 2009/125/EC of the European Parliament and of the Council with regard to Ecodesign requirements for Space heaters and combination heaters with Prated < 400kW - COMMISSION REGULATION (EU) N° 813/2013 of 2 August 2013

(6): According ISO 9614:2009. Eurovent conditions, with 1pW reference sound power (without accessories)

(7): Basic unit without accessories



## Improve Operations

Technology is continuously evolving and Trane Engineering is ahead of the curve in bringing innovation into product development. Our sustainable solutions deliver enhancements to the Trane installed base to make your chillers and heat pumps even "better than before". That's Trane Building Advantage - TBA.

## Trane Rental Services

Cooling and heating are services, not products. A process or a building does not need a chiller or a boiler sitting on a roof, but a reliable and efficiency supply of cold or hot water, cold or warm air. This is the essence of what we do at Trane Rental Services. Let us take care of it for you.



**Read more <https://trane.eu/rental>**

Trane has a policy of continuous product and product data improvement and reserves the right to change design and specifications without notice.



Trane – by Trane Technologies (NYSE: TT), a global climate innovator – creates comfortable, energy efficient indoor environments through a broad portfolio of heating, ventilating and air conditioning systems and controls, services, parts and supply. For more information, please visit [trane.eu](https://trane.eu) or [tranetechnologies.com](https://tranetechnologies.com).