

Athens the	<b>03.08.2017</b>
Inspection Lot	<b>020000435767</b>
Sales Order No	<b>15008204 / 230</b>
Delivery Document	<b>0085150720</b>
Certificate No	<b>1000321556</b>
Customer's Ref No	<b>LOADING 02/08</b>

*Declaration of Conformity  
according to EN 1655*

## **DECLARATION OF CONFORMITY**

The products, listed here-below in the shown quantities, are made from *Cu-DHP* and conform to the specifications *EN 1057 R290*. as well as to the conditions and requirements of the purchaser *COPPER COM D.O.O.*.

Designation	<b>COPPER TUBES 028,000x1,00x5000, STRAIGHT, FOR SANITARY USE,</b>
Quantity	<b>544,00 KG</b>

The quality assurance system applied to monitor the production of the above products, is in compliance to the requirements of ISO 9001/2008 and independently certified by TUV HELLAS, with registration No 041070119.

The Q.A. Manager



**D. SKARMOUTSOS**

ISSUE B

REV 0

DATE SEP-2007

FORM N1

e-mail: info@halcor.com  
website: www.halcor.com  
VAT number: EL094061318

**Offices @ Copper Tube Plant (Mailing Address)**  
62<sup>nd</sup> km Athens-Lamia National Road,  
GR-32011 Inofita-Viotia, GREECE  
Tel.: +30 22620 48111, Fax: +30 22620 48911

**Foundry**  
60<sup>th</sup> km Athens-Lamia National Road,  
GR-32011 Inofita-Viotia, GREECE  
Tel.: +30 22620 53479, Fax: +30 22620 53925

**Domestic Sales Dept**  
252 Pireos str.  
GR-17778, Tavros, Athens, GREECE  
Tel.: +30 210 4898111, Fax: +30 210 4898397



HALCOR S.A., 57th km National Road Athens-Lamia,  
GR 32011 Inofyta Viotias

08  
001 CPR 06.2013

**EN 1057**

Seamless, round copper tubes for water and gas in sanitary and heating applications

Intended to be used in :

- Drainage, and disposal of other liquids and gaseous waste;
- Supply of fuels, oil and other liquids (including hot water heating systems);
- Fire suppression and extinguishing systems;
- Supply of gases, pressure and vacuum systems;
- Storage fixtures.

Product designation:

**COPPER TUBES 028,000x1,00x5000, STRAIGHT, FOR SANITARY USE,**

Reaction to fire:	Class A.1
Crushing strength:	NPD
Internal pressure:	NPD
Dimensional tolerances:	pass
Resistance to high temperature:	Suitable for use to 120 °C
Weldability:	pass
Tightness: gas and liquid:	pass
Durability of crushing strength,	