

## Declaration of Performance No. 0551-CPR-2013-074

Unique identification code of the product-type: ArmaFlex ACE Plus

Intended use/es: Thermal insulation of building equipment and

industrial installations (ThiBEII)

**Manufacturer:** Armacell Poland Sp.zo.o.

UI. Targowa 2

PL-55-300 Środa Śląska

System/s of AVCP: 1 and 3

Harmonised standard: EN 14304:2009+A1:2013

Notified body/ies: NB 0919

Declared performance/s:

Essential characteristics	Performance		
Thermal resistance / Thermal conductivity	Tape, Sheets	$d_N = 3 - 50 \text{ mm}$	$\lambda_{0^{\circ}C} \le 0.035 \text{ W/(m * K)}$ $\lambda(\theta_{\text{m}}) = (35 + 0.1 \cdot \theta_{\text{m}} + 0.0008 \cdot \theta_{\text{m}^2}) / 1000$
Reaction to fire	Tape, Sheets	$d_{N} = 3 - 50 \text{ mm}$	B - s3, d0
Durability of thermal resistance against ageing/ degradation	Dimensional stability <sup>1)</sup> Minimum service temperature ST(-)-50 (= -50 °C)		
Durability of thermal resistance against high temperatures	Maximum service temperature ST(+)110 (=110°C)		
Durability of reaction to fire against ageing/ degradation	Durability characteristics <sup>2)</sup>		
Durability of reaction to fire against high temperature	Durability characteristics <sup>2)</sup>		
Water permeability	NPD		
Water vapour permeability/ Water vapour diffusion resistance	Tape, Sheets	$d_{N} = 3 - 32 \text{ mm}$	$\mu$ 10000 ( $\mu \ge 10000$ )
	Sheets	$d_N = 33 - 50 \text{ mm}$	$\mu$ 7000 ( $\mu \ge 7000$ )
Rate of release of corrosive substances	NPD		
Acoustic absorption index	NPD		
Release of dangerous substances to indoor environment	NPD 3)		

<sup>1)</sup> The thermal conductivity of flexible elastomeric foam does not change with time

This declaration of performance is made available in accordance with Article 7(3) of Regulation (EU) No 305/2011 on our homepage: <a href="http://www.armacell.com/DoP">http://www.armacell.com/DoP</a>

The fire performance of flexible elastomeric foam products does not change with time.

European test methods are under development.

<sup>4)</sup> No Performance Determined (NPD)



The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Georg, Eleftheriadis, Technical Marketing Manager EMEA Sroda, 25.11.2020

[signature]