



AD482MJERAF
AD722MTERAF
AD962MTERAF



Optional controller
HW-BA116ABK



Optional controller
HW-BA101ABT



Optional controller
YR-E17A



optional remote control YR-HRS01
(RE-02 remote control receiver)



Optional controller
YR-E16B

- Static pressure selection (16 speed for AD722/962MTERAF and 10 speed for AD482MJERAF)
- Can be installed together with other indoor units on the same refrigerating circuit, to pre-treat the outdoor air before sending it to indoor units or in the environment.
- Please notice that the nominal potential in heating is always lower than that of cooling.
- Integrated flow switch.

Model		AD482MJERAF	AD722MTERAF	AD962MTERAF
Capacity				
Cooling	kW	14,00	22,60	28,00
Heating	kW	8,90	15,20	17,80
Electrical Parameters				
Power supply	Ph/V/Hz	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
Ventilation				
Air flow (H/M/L)	m ³ /h	1600/1460/1070	4000/3500/3000	4500/4000/3600
Sound pressure (H/M/L)	dB(A)	48/47/42	50/47/44	51/48/45
Sound power (H/M/L)	dB(A)	61/60/56	68/65/60	68/66/62
Installation – Dimensions				
Net dimensions (WxDxH)	mm	1500x700x248	1512x856x502	11512x856x502
Packaged unit dimensions (WxDxH)	mm	1718x848x345	1558x896x612	1558x896x612
Net/gross weight	Kg	43,6/50,4	102,0/116,0	102,0/116,0
Ø Liquid pipe	mm (inch)	9,52 (3/8)	12,70 (1/2)	12,70 (1/2)
Ø Gas pipe	mm (inch)	15,88 (5/8)	22,22 (7/8)	22,22 (7/8)
Static pressure (Standard/Max.)	Pa	100/200	100/250	100/250