

ARNU30GSRA4 / ARNU36GSRA4



MODEL		UNIT	ARNU30GSRA4	ARNU36GSRA4
Cooling Capacity		kW	8.8	10.4
Heating Capacity		kW	9.4	10.8
Power Input (H / M / L)	Nominal	W	47.0 / 42.0 / 36.0	65.0 / 47.0 / 42.0
Exterior Color		-	Magic White	Magic White
RAL Code		-	RAL 9016	RAL 9016
Dimensions (W x H x D)	Body	mm	1,200 x 360 x 265	1,200 x 360 x 265
	Shipping	mm	1,280 x 360 x 455	1,280 x 360 x 455
Fan	Type	-	Cross Flow Fan	Cross Flow Fan
	Motor Output x Number	W x No.	113 x 1	113 x 1
	Air Flow Rate (H / M / L)	m³/min	21.0 / 17.0 / 13.0	25.0 / 21.0 / 17.0
	Motor Type	-	BLDC	BLDC
Air Filter		-	Pre-Filter	Pre-Filter
Pipe Connections	Liquid Side	mm (inch)	Ø9.52 (3/8)	Ø9.52 (3/8)
	Gas Side	mm (inch)	Ø15.88 (5/8)	Ø15.88 (5/8)
	Drain Pipe (Internal Dia.)	mm (inch)	Ø14.5 (9/16)	Ø14.5 (9/16)
Weight	Body	kg	16.6	16.6
Sound Pressure Levels (H / M / L)		dB(A)	46.0 / 42.0 / 38.0	51.0 / 46.0 / 42.0
Sound Power Levels (H / M / L)		dB(A)	60.0 / 55.0 / 50.0	63.0 / 60.0 / 55.0
Power Supply		V / Ø / Hz	220 - 240, 1, 50 - 60	220 - 240, 1, 50 - 60
Transmission Cable		mm²	1.0 ~ 1.5 x 2C	1.0 ~ 1.5 x 2C

Note :

1. Performance tested under EN14511

2. Capacities are based on the following conditions

- Cooling : Indoor temp. 27°C (80.6°F) DB / 19°C (66.2°F) WB, Outdoor temp. 35°C (95°F) DB / 24°C (75.2°F) WB, Interconnecting piping length 7.5m, Level difference of zero
- Heating : Indoor temp. 20°C (68°F) DB / 15°C (59°F) WB, Outdoor temp. 7°C (44.6°F) DB / 6°C (42.8°F) WB, Interconnecting piping length 7.5m, Level difference of zero

3. Due to our policy of innovation, some specifications may be changed without notification

Accessories

CHASSIS	ARNU30GSRA4	ARNU36GSRA4
Drain Pump	-	-
Cassette Cover	-	-
Refrigerant Leak Detector	PRLDNVS0 (R410A), PLDRNV1S (R32)	
EEV Kit	-	-
Multi-tenant Power Module	PINPMB001	
Robot Cleaner	-	-
Pre Filter (Washable)	○	○
Ion Generator	-	-
CO ₂ Sensor	-	-
Ventilation Kit	-	-
IR Receiver	-	-
Zone Controller	-	-
Dry Contact (with additional accessory)	PDRYCB000 (1 point contact), PDRYCB320, PDRYCB400 (2 points input), PDRYCB500 (Modbus)	
External Input (1 point)	○	○
Wi-Fi	○	○

※ ○ : Applied, - : Not applied

Option : Refer to model name in table

1) External installation only

STANDARD

INDOOR UNITS

WALL MOUNTED