



LG participates in the ECP programme for EUROVENT AC program. Check ongoing validity of certification : [www.eurovent-certification.com](http://www.eurovent-certification.com)

OUTDOOR UNITS				MU2R15.U13	MU2R17.U13
Compressor	Type			Twin Rotary	Twin Rotary
Capacity**	Cooling	Min. / Nom. / Max.	kW	0.9 / 4.1 / 4.7	0.9 / 4.7 / 5.4
	Heating	Min. / Nom. / Max.	kW	1.0 / 4.7 / 5.4	1.0 / 5.1 / 5.5
Low Temperature Capacity	Heating -7°C	Max.	kW	3.7	4.0
Power Input**	Cooling	Min. / Nom. / Max.	kW	0.2 / 1.0 / 1.4	0.2 / 1.2 / 1.8
	Heating	Min. / Nom. / Max.	kW	0.2 / 1.1 / 1.5	0.2 / 1.2 / 1.5
Running Current	Cooling	Min. / Nom. / Max.	A	1.0 / 4.4 / 6.2	1.0 / 5.4 / 8.0
	Heating	Min. / Nom. / Max.	A	1.1 / 4.7 / 6.5	1.1 / 5.3 / 6.7
EER				4.10	3.84
COP				4.40	4.25
SEER				8.60	8.50
SCOP				4.61	4.61
Pdesign (@-10°C)			kW	3.60	3.60
Seasonal Energy Label	Cooling / Heating (A+++ to D Scale)			A+++ / A++	A+++ / A++
Annual Energy Consumption	Cooling / Heating			167 / 1,095	193 / 1,095
Airflow Rate	Nom.		m <sup>3</sup> /min	35	35
Sound Pressure*	Cooling	Nom.	dB(A)	45	46
	Heating	Nom.	dB(A)	48	49
Sound Power	Cooling	Max.	dB(A)	60	61
Dimensions	W x H x D		mm	770 x 545 x 288	770 x 545 x 288
Net Weight			Kg	32.5	32.5
Refrigerant	Type			R32	R32
	Charge		Kg	1.04	1.04
	Additional Charge		g/m	-	-
	GWP			675	675
	t-CO <sub>2</sub> eq			0.702	0.702
Operation Range (Outdoor)	Cooling	Min. / Max.	°C DB	-10 / 48	-10 / 48
	Heating	Min. / Max.	°C WB	-15 / 18	-15 / 18
Power Supply			Ø / V / Hz	1 / 220-240 / 50	1 / 220-240 / 50
Power Supply Cable			No. x mm <sup>2</sup>	3C x 2.5	3C x 2.5
Transmission Cable			No. x mm <sup>2</sup>	4C x 0.75	4C x 0.75
Circuit Breaker			A	13	13
Piping Length Total			m	30	30
Piping Length per Branch		Max.	m	20	20
Piping Elevation Difference	IDU - ODU	Max.	m	15	15
	IDU - IDU	Max.	m	7.5	7.5
Piping Connection	Liquid		mm (inch) x No.	Ø6.35 (1/4) x 2	Ø6.35 (1/4) x 2
	Gas		mm (inch) x No.	Ø9.52 (3/8) x 2	Ø9.52 (3/8) x 2