



LG participates in the ECP programme for EUROVENT AC program. Check ongoing validity of certification : [www.eurovent-certification.com](http://www.eurovent-certification.com)

kBtu/H	5	7	9	12	15	18	24
kW	1.5	2.1	2.6	3.5	4.2	5.3	7.0
Low Static Pressure	-	-	-	-	-	-	-

○◎ CL24FN30

● Multi Only ○◎ Compatible with Residential Single Split ○◎ Compatible with Commercial Single Split

### Duct (Low Static)

INDOOR	CL24F-N30	
Capacity	Cooling / Heating	Norm. kW
Power Input	H / M / L W	6.8 / 7.5
Running Current	H / M / L A	15.0 / 13.0 / 11.0
Power Supply	Ø / V / Hz	0.65 / 0.56 / 0.47
Air Flow Rate	H / M / L m <sup>3</sup> /min	1 / 220-240 / 50
Sound Pressure*	H / M / L dB(A)	20.0 / 16.0 / 12.0
Sound Power Level	Rated dB(A)	39 / 35 / 32
Dehumidification Rate	l/h	58
Dimensions	W x H x D mm	2.5
Net Weight	kg	1,100 x 190 x 700
Piping	Liquid Side mm (inch)	26.0
Connections	Gas Side mm (inch)	Ø9.52 (3/8)
External static pressure	Min. ~ Max. Pa (mmAq)	Ø15.88 (5/8)
		0 - 5 (0 - 50)
<b>ACCESSORIES &amp; OTHERS</b>		<b>CL24F-N30</b>
Commercial Single Split Compatible		Y
Dual Vane Cassette Panel		-
Air Purification Kit (UVnano Filter Box)		Y
Dry Contact		Y
Wireless or Wired Remote Controller		Y
ThinQ (Wi-Fi)		Y